

**R307036 FM Connection Box Splash Line IP54, 87x87, 2x1-Port, white**

---

010.2266

**Description**

Color: pure white (RAL 9010).

**Scope of supply**

- Foam-rubber padded mounting frame
- Cover frame
- Round central plate including O-ring and fastening screws
- Label strips
- Label window
- Instruction manual

**Weight**

112.000G

**Technical Data**

---

Distributor, housing type	Housing
Application area	Flush-mounting (FM)
Color code RAL	9010
Color	pure white
Assembly	empty
Dimensions	87 x 87 mm
Protection class (IP)	54

**Tender text**

---

FM Connection Box Splash Line IP54, 87x87, 2x1-port, white  
Housing, frame and cover are made of high-grade, impact-resistant thermoplast (polyester). This is a dimensionally stable, gasoline and oil resistant, and thermally stable material; temperature limit for one hour is -50°C and +100°C. The connection box features one module holder for RJ45/E-2000™-Compact/SC-RJ, and is designed to accommodate the R&M security and the R&M environment system. The security system's 3-level protection concept comprises optionally visual coding, combined mechanical-visual coding or the locking of individual ports.

## Features:

- Mounting track: 56 x 56 mm
- Protection class: IP54 acc. to IEC 60529 in combination with the Splash cap and the Splash sleeve
- Temperature range: -25°C to +80°C
- Color: pure white (RAL 9010)

**Modules & Accessories**

R925371	Connection Module Cat.5e, 1xRJ45/u, 10x
R925370	Connection Module Cat.5e, 1xRJ45/s, 10x
R302373	Connection Module Cat.6, 1xRJ45/u, 10x
R313064	Connection Module Real10 Cat.6, 1xRJ45/u, 10x
R302372	Connection Module Real10 Cat.6, 1xRJ45/s, 10x
R509500	Connection Module Cat.6A ISO, 1xRJ45/u, 10x
R509504	Connection Module Cat.6A ISO, 1xRJ45/s, 10x
R306063	Splash Cap IP54, white
R306058	Splash Cap IP54, blue
R306062	Splash Cap IP54, red
R306060	Splash Cap IP54, yellow
R306061	Splash Cap IP54, green
R310726	Cable Gland IP67, M20, 5.5-12mm, plastic
R309022	Adapter Collar for FM Splash Outlet