

SC

Ordering information: SC connector

Connector type	Polishing	Insertion loss ¹⁾ [dB] (mean/97%)	Cable Ø [mm]	Type
SM High-End	PC/UPC	0.12/0.25	≤ 3.5	FSC-CMAX-A101
SM High-End	APC	0.12/0.25	≤ 3.5	FSC-CMAX-A600
SM High-End	APC 9°	0.12/0.25	≤ 3.5	FSC-CMAX-A603
SM premium	PC/UPC	0.06/0.15	≤ 3.5	FSC-CMAX-H101
SM premium	APC	0.06/0.15	≤ 3.5	FSC-CMAX-H600
G50/125, G62.5/125	PC	0.20/0.50	≤ 3.5	FSC-CMAX-B101
HCS200/230	PC	0.30/0.75	≤ 3.5	FSC-CMAX-D101

¹⁾ Each-to-each IEC 61300-3-34 method 2

SC-QXA connectors see page 85

Ordering information: SC adapter

Adapter type	Mounting	Sleeve material	Colour	Type
SM	with 2-hole flange	zirconia ceramic	blue	FSC-FSC-D100
SM APC	with 2-hole flange	zirconia ceramic	green	FSC-FSC-D600
MM	with 2-hole flange	phosphor-bronze	beige	FSC-FSC-D200
Flangeless SM	integrated fixing spring	zirconia ceramic	blue	FSC-FSC-A100
Flangeless SM	integrated fixing spring	zirconia ceramic	black	FSC-FSC-A101
Flangeless APC	integrated fixing spring	zirconia ceramic	green	FSC-FSC-A600
Flangeless MM	integrated fixing spring	phosphor-bronze	beige	FSC-FSC-A200