Rack Power Distribution

- World Wide Products -

Quick reference – updated November 2012



Product Feature by Rack PDU Family/Series	Basic	Mete	ered	Sı	witched	Metered by Outlet with Switching
		AP7800 Series	AP8800 Series	AP7900 Series	AP8900 Series	AP8600 Series
	Design	Features				
Ultra low profile, space saving design	1	V	V	V	√	V
Hydraulic-Magnetic circuit breakers (in units configured with circuit preakers)	٧	√	٧	√	1	1
Ultra Low Profile circuit breakers (for units with breakers)			√		√(not AP8965)	
Locking IEC receptacles and locking power cord compatible			V		√	V
Environmental monitoring port for external temperature/humidity monitoring			4		1	1
Displa	y and Netw	ork Manage	ement			
Full featured network management capability via web, SNMP, telnet		√	V	V	√	V
2 digit, 7-segment LED display		V		V		
User interactive LCD display for local access			V		1	V
Network Port Sharing (Up to 4 rack PDUs share one IP address in			ا		-1	-1
one enclosure)			V		V	٧
Local USB Port for Easy Local Firmware Updates			√		√	√
	Metering	Capability				
Active Current Measurements (amps)		√	√	√	√	√
Active Power Measurements (Including volts, amps, real power kW, and energy kWh)			1		√	√
User customizable alarms and warnings		√	√	√	√	√
Embedded log memory to record/review/report historic metered		7	V	V	√	V
data		,	· ·	'	*	,
Individual Outlet Power Metering	0 11 1					٧
	Outlet	Control		, ,	1 /	1
Individual outlet remote power on/off control				, v	Y	٧
Power On sequencing and time delays with full user customization				٧	٧	٧
Outlet level grouping (multiple outlets in same or multiple units follow single command)				√	√	√
User Access control with assignable roles, access levels at device				-1	-1	.1
and outlet level				٧	٧	٧
Outlet grouping feature for synchronized control of outlets on multiple Rack PDUs				√	1	√
	ntenance an	d Upgradeabi	lity			
Redundant internal power supply for improved Switched Rack PDU reliability				√	1	√
Field replaceable network management module		_	√		1	1



Metered Rack PDUs

	Mounting U-Space	Nominal Voltage	Region	Input Circuit	Nominal Power	Inpu	t Plug Type	Outpu	t Receptacles	Cord Length	APC SKU			
		100-120	NAM	15A	1.4kW	•	NEMA 5-15P	@	(16)5-15	3.0 m	AP7831			
		120	NAM	20A	1.9kW	3	NEMA L5-20P	•	(24)5-20	3.0 m	AP7830			
100-120V Input	Vertical, 0U	100	Japan	20A	2.0kW	(3)	NEMA L5-20P	@	(24) 5-15	3.0 m	AP7830J			
<u>=</u>		100	Japan	30A	2.4kW	3	NEMA L5-30P	@	(24) 5-15	3.0 m	AP7832J			
á		120	NAM	30A	2.9kW	ூ	NEMA L5-30P	•	(24)5-20	3.0 m	AP7832			
7	Horizontal, 1U	120	NAM, LAM	15A	1.4kW	8	NEMA 5-15P	@	(8)5-15	3.6 m	AP7800			
유	Tionzontal, io	120	NAM, LAM	20A	1.9kW	⊛	NEMA L5-20P	•	(8)5-20	3.6 m	AP7801			
	Horizontal, 2U	120	NAM, LAM	30A	2.9kW	⊚	NEMA L5-30P	•	(16)5-20	3.6 m	AP7802			
	Tionzonkai, zo	100	Japan	30A	3.0kW	3	NEMA L5-30P	(A)	(16) 5-15	3.6 m	AP7802J			
		230	Worldwide	10/15A	2.3kW	60	IEC-320 C14	- 50	(16)C13	3.0 m	AP7850			
		100-240	NAM, LAM	20A	3.3kW	➂	NEMA L6-20P		(18)C13, (2)C19	3.0 m	AP8858NA3			
		100-240	Worldwide	16A	3.3kW		IEC-320 C20	₩ 🕾	(18)C13, (2)C19	Inlet	AP8858			
ā	Vertical, 0U	100-240	EMEA, APJ,	16A	3.7kW	0	IEC309 16A		(18)C13, (2)C19	3.0 m	AP8858EU3			
든		200-240	NAM, Japan,	30A	5.0kW	(3)	NEMA L6-30P		(36)C13, (6)C19	3.0 m	AP8841			
200-240V Input		220-240	EMEA, APJ, LAM, GCN	32A	7.4kW	0	IEC309 32A	₩ 🖫	(36)C13, (6)C19	3.0 m	AP8853			
ĕ	Horizontal, 1U	100-240	Worldwide	10/15A	2.5kW	8	IEC-320 C14		(8)C13	Inlet	AP7820			
	Holizolital, io	100-240	Worldwide	16A	3.3kW	-	IEC-320 C20	•	(8)C13	Inlet	AP7821			
	Horizontal, 2U	200-240	NAM	30A	5.0kW	③	NEMA L6-30P		(12)C13, (4)C19	3.6 m	AP7811			
	Holizolital, 20	230	EMEA, APJ,	32A	7.4kW	0	IEC309 32A		(12)C13, (4)C19	3.6 m	AP7822			
				***	200		004.04	E 70.14	_	NES 44 1 04 00E	-	(40)E 00	1.0 m	AP7862
		208	NAM	20A, 3Φ	5.7kW	⊕	NEMA L21-20P	•	(42)5-20	3.0 m	AP7892			
		000			57111	_	1151 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		/00E 00 /0V 0 00	1.0 m	AP7863			
		208	NAM	20A, 3Φ	5.7kW	⊛	NEMA L21-20P	⊕ ③	(21)5-20, (6)L6-20	3.0 m	AP7893			
5		208	NAM	20A, 3Φ	5.7kW	⊛	NEMA L21-20P	⊕ 🕾	(36)C13, (6)C19, (2)5-20	1.8 m	AP8861			
울		208	Japan	20A, 3Φ	6.0kW	•	NEMA L21-20P	6	(42) 5-15	1.0 m	AP7862J			
208V 3-phase Input	Vertical, 0U	208	NAM	30A, 3Φ	8.6kW	•	NEMA L21-30P		(36)C13, (6)C19, (2)5-20	1.8 m	AP8865			
6		200-240	NAM	50A, 3Φ	10.0kW	⊕	CS8365C		(36)C13, (6)C19	1.8 m	AP8868			
≳		200-240	NAM	50A, 3Φ	14.4kW	(₽)	CS8365C		(24)C13, (4)C19,	1.0 m	AP7869			
8		200-240	NAM	1 300,34	14.4KW	9	C30303C	•	(2)L6-30	3.0 m	AP7899			
		200-240	NAM	50A, 3Φ	14.4kW	⊗	CS8365C	•	(6)C19	1.8 m	AP7867A			
		200-240	NAM	60A, 3Φ	17.3kW	•	IEC309-60A 3P+PE	₩ 🖫	(6)C13, (12)C19	1.8 m	AP8866			
		200-240	NAM	1 60A, 34	Ir.skw	0	IEC309-60A 3P+PE	9	(30)C13	1.8 m	AP8867			
		400-415	Worldwide	16A, 3Φ	11kW	0	IEC309-16A 3P+N+PE	∞ 🖫	(36)013, (6)019	1.8 m	AP8881			
ېږ nput		415	NAM	30A, 3Φ	17.3kW	0	IEC309-30A 3P+N+PE	₩ 🖫	(30)C13, (12)C19	1.8 m	AP8887			
400-415V 3-phase Input	Vertical, 0U	400	EMEA, APJ, LAM, GCN	32A, 3Φ	22kW	⊕	IEC309-32A 3P+N+PE	₩ 🖫	(30)C13, (12)C19	1.8 m	AP8886			
4 9		400	EMEA, APJ, LAM, GCN	32A, 3Φ	22kW	0	IEC309-32A 3P+N+PE	•	(6)C19	1.8 m	AP7855A			
		415	NAM	40A, 3Φ	23kW	0	IEC309-60A 3P+N+PE	₩ 🖶	(30)013, (12)019	1.8 m	AP8888			



AP8841

Metered by Outlet with Switching Rack PDUs

	Mounting U-Space	Nominal Yoltage	Region	Input Circuit	Nominal Power	Inpu	t Plug Type	Outpu	t Receptacles	Cord Length	APC SKU
		208	NAM	20A	3.3kW	3	NEMA L6-20P	₩ 🖫	(21)C13, (3)C19	3.0 m	AP8659NA3
Input		100-240	Worldwide	20A	3.3kW	*	IEC-320 C20	₩ 🖀	(21)013, (3)019	Inlet	AP8659
40V In		230	EMEA, APJ, LAM, GCN	16A	3.7kW	0	IEC309 16A	₩ 🖫	(21)C13, (3)C19	3.0 m	AP8659EU3
200-240V		200-240	NAM, Japan, LAM	30A	5.0kW	39	NEMA L6-30P	₩ 🖫	(21)C13, (3)C19	3.0 m	AP8641
	Vertical, 0U	220-240	EMEA, APJ, LAM, GCN	32A	7.4kW	0	IEC309 32A	₩ 🖫	(21)C13, (3)C19	3.0 m	AP8653
208V 3- phase		208	NAM	20A, 3Φ	5.7kW	9	NEMA L21-20P	59 🖫	(21)C13, (3)C19	1.8 m	AP8661
400- 415V 3-phase		400-415	Worldwide	16A, 3¢	11kW	•	IEC309-16A 3P+N+PE	₽ ₽	(21)C13, (3)C19	1.8 m	AP8681

Switched Rack PDUs

	Mounting U-Space	Nominal Yoltage	Region	Input Circuit	Nominal Power	Inpu	t Plug Type	Outpu	it Receptacles	Cord Length	APC SKU
		100-120	NAM	15A	1.4kW	6	NEMA 5-15P	6 0	(16)5-15	3.0 m	AP7931
		120	NAM, LAM	20A	1.9kW	(3)	NEMA L5-20P	•	(24)5-20	3.0 m	AP7930
ă	Vertical, 0U	100	Japan	20A	1.9kW	3	NEMA L5-20P	®	(24) 5-15	3.0 m	AP7930J
ੂ	[120	NAM, LAM	30A	2.9kW	③	NEMA L5-30P	•	(24)5-20	3.0 m	AP7932
á		100	Japan	30A	3.0kW	9	NEMA L5-30P	0	(24) 5-15	3.0 m	AP7932J
100-120V Input	Horizontal, 1U	100-120	NAM, LAM	15A	1.4kW	8	NEMA 5-15P	0	(8)5-15	3.6 m	AP7900
유	Tionzontal, 10	100-120	NAM	20A	1.9kW	➂	NEMA L5-20P	•	(8)5-20	3.6 m	AP7901
	Horizontal, 2U	120	NAM	30A	2.9kW	•	NEMA L5-30P	- 69	(16)5-20	3.6 m	AP7902
	Tionzontal, 20	100	Japan	32A	3.0kW	➂	NEMA L5-30P	6	(16) 5-15	3.6 m	AP7902J
		230	EMEA, APJ,	10A	2.3kW	8	IEC C14	₩.	(16)C13	3.0 m	AP7950
	[100-240	NAM, LAM	20A	3.3kW	•	NEMA L6-20P		(7)C13, (1)C19	3.0 m	AP8958NA3
		100-240	Worldwide	16A	3.3kW	E	IEC-320 C20		(7)C13, (1)C19	Inlet	AP8958
		230	EMEA, APJ, LAM, GCN	16A	3.7kW	0	IEC309 16A	₩ 🕾	(7)C13, (1)C19	3.0 m	AP8958EU3
	Vertical, 0U	100-240	NAM, LAM	20A	3.3kW	③	NEMA L6-20P		(21)C13, (3)C19	3.0 m	AP8959NA3
ă	vertical, 00	100-240	Worldwide	16A	3.3kW	E	IEC-320 C20		(21)C13, (3)C19	Inlet	AP8959
200-240V Input		230	EMEA, APJ, LAM, GCN	16A	3.7kW	0	IEC309 16A	₩ 🕾	(21)C13, (3)C19	3.0 m	AP8959EU3
2	1	200-240	NAM, Japan,	30A	5.0kW	3	NEMA L6-30P		(21)C13, (3)C19	3.0 m	AP8941
20		220-240	EMEA, APJ, LAM, GCN	32A	7.4kW	0	IEC309 32A	₩ 🖫	(21)C13, (3)C19	3.0 m	AP8953
	Horizontal, 1U	208-230	Worldwide	10/15A	2.5kW		IEC-320 C14		(8)C13	2.0 m	AP7920
	Horizontal, 10	208-230	Worldwide	16A	3.3kW	E	IEC-320 C20	- 50	(8)C13	2.4 m	AP7921
		200-240	NAM	30A	5.0kW	⊚	NEMA L6-30P	9	(16)C13	3.6 m	AP7911A
	Horizontal, 2U	230	EMEA, APJ, LAM, GCN	32A	7.4kW	0	IEC309 32A	•	(16)C13	3.6 m	AP7922
		208	NAM	20A, 3Φ	5.7kW	③	NEMA L21-20P	•	(24)5-20	1.0 m	AP7960
Š		200	NAM	204,34	3.7KW	_	NEINA CZI-ZOF	•	(24)0-20	3.0 m	AP7990
/3-ph Input	Vertical, 0U	208	NAM	20A, 3Φ	5.7kW	⊕	NEMA L21-20P		(21)C13, (3)C19	1.8 m	AP8961
5 ₫	Yerrioa, oo	208	NAM	30A, 3Φ	8.6kW	•	NEMA L21-30P		(21)C13, (3)C19	1.8 m	AP8965
208V 3-phase Input	[200-240	NAM	50A, 3Φ	12.5kW	(Đ)	CS8365C		(21)C13, (3)C19	1.0 m	AP7968
		200-240	14/-11-1	3011, 34	IE.OK W	•		₩ 🖫	(2.,510, (0,510	3.0 m	AP7998
400- 415V 3-phase	Vertical, 0U	400-415	Worldwide	16A, 3Φ	11kW	⊕	IEC309-16A 3P+N+PE	₩ 🕾	(21)C13, (3)C19	1.8 m	AP8981



AP8941

Rack Automatic Transfer Switch

	Mounting U-Space	Input Circuit			Cord Length	APC SKU
100V	1	20A	NEMA L5-20P	(8) 5-15	8 ft.	AP7752J
100/ 120 V	1	15A	NEMA 5-15P	(8)5-15	8 ft.	AP7750A
•.	1	20A	NEMA L5-20P	(10)5-20	8 ft.	AP7752
120 ¥	2	30A	NEMA L5-30P	(16)5-20	8 ft.	AP7753
200- 208 ¥	1	20A	NEMA L6-20P	(8)C13, (1)C19	8 ft.	AP7730
202	2	30A	NEMA L6-30P	(16)C13, (2)C19	8 ft.	AP7732
208V	2	30A	NEMA L6-30P	(1) L6-30R	8 ft.	AP7731
208/230 V	1	15A	IEC C14 Inlet	(12)C13	none	AP7721
208	1	20A	IEC C20 Inlet	(8)C13, (1)C19	none	AP7723
۵.	1	16A	(2) IEC-309	(1) IEC-309	3 ft.	AP7722A
230 V	2	32A	IEC-309	(16)/013, (2)/019	8 ft.	AP7724
208V 3Ф	1	20A, 3¢	NEMA L21-20P	(1) L21-20R	3 ft.	AP7701







Basic Rack PDUs

	Mounting U-Space	Nominal Yoltage	Region	Input Circuit	Nominal Power	Inpu	t Plug Type	Outpu	t Receptacles	Cord Length	APC SKU
		100-120	NAM, LAM	15A	1.4kW	®	NEMA 5-15P	@	(14)5-15	3.6 m	AP9567
		120	NAM	20A	1.9kW	3	NEMA L5-20P	•	(24)5-20	3.0 m	AP7530
=	Vertical, 0U	100-120	NAM	20A	1.9kW	(3)	NEMA L5-20P	6	(14)5-15	3.6 m	AP9551
츌	vertical, 00	100-120	Japan	20A	2.0kW	3	NEMA L5-30P	6	(24) 5-15	3.0 m	AP7530J
100-120V Input		120	NAM	30A	2.9kW	③	NEMA L5-30P	•	(24)5-20	3.0 m	AP7532
5		100	Japan	30A	3.0kW	3	NEMA L5-30P	<u> </u>	(24) 5-15	3.0 m	AP7532J
ġ		100-120	NAM, LAM	15A	1.4kW	®	NEMA 5-15P	6	(10)5-15	3.6 m	AP9562
-	Horizontal, 1U	100-120	NAM	20A	1.9kW	•	NEMA 5-20P	•	(10)5-20	3.6 m	AP9563
	Tionzontal, io	100-120	NAM	20A	1.9kW	➂	NEMA L5-20P	•	(10)5-20	3.6 m	AP9564
		100-120	NAM	30A	2.9kW	➂	NEMA L5-30P	•	(10)5-20	3.6 m	AP9560
		120-240	Worldwide	10A	2.3kW	8	IEC C14	- 69	(15)C13	2 m	AP9568
	l ī	120-230	Worldwide	16A	3.3kW	1	IEC-320 C20	•	(15)C13	2.5 m	AP9572
		200-240	NAM	20A	3.3kW	③	NEMA L6-20P		(20)C13, (4)C19	3.0 m	AP7540
	Ι Γ	230	EMEA, APJ,	16A	3.7kW	0	IEC309 16A	-	(20)C12 (4)C10	1.0 m	AP7551
	Vertical, 0U	230	LAM, GCN	16A	3.7KW	Ψ	IEC303 IOA	☞ 🐨	(20)C13, (4)C19	3.0 m	AP7554
4	l ī	230	Worldwide	16A	3.7kW	E	IEC C20		(20)C13, (4)C19	3.0 m	AP7552
훁	l i	200-240	NAM	30A	5.0kW	(3)	NEMA L6-30P		(20)C13, (4)C19	3.0 m	AP7541
200-240V Input		230	EMEA, APJ, LAM, GCN	32A	7.4kW	0	IEC309 32A	₩ 🖫	(20)C13, (4)C19	3.0 m	AP7553
ģ		208	NAM, LAM	20A	3.3kW	E	NEMA L6-20P		(12)C13	3.6 m	AP9566
-	l [120-240	Worldwide	16A	3.7kW	E	IEC C20	₩ 🖫	(10)C13, (2)C19	2.5 m	AP9559
	Horizontal, 1U	100-240	Worldwide	16A	3.7kW	=	IEC C20		(12)C13	2.5 m	AP9565
		208	NAM	30A	5.0kW	3	NEMA L6-30P		(4)C19	3.0 m	AP9570
		200-240	NAM, LAM	30A	5.0kW	(3)	NEMA L6-30P		(10)C13	3.6 m	AP9571A
	Horizontal, 2U	230	EMEA, APJ,	32A	7.4kW		hardwire		(4)C19	8.5 m	AP7585
	Holizolikal, 20	230	EMEA, APJ,	32A	7.4kW		hardwire	0	(4)IEC 309 32A	8.5 m	AP7586
		208	NAM		50111	_		_	44005.00	1.0 m	AP7562
		208	NAM	20A, 3Φ	5.8kW	⊛	NEMA L21-20P	•	(42)5-20	3.0 m	AP7592
		208	NAM	20A, 3Φ	5.8kW	(3)	NEMA L21-20P	® ®	(21)5-20, (6)L6-20	1.0 m	AP7563
		208	NAM	20A, 3Φ	5.8kW	⊕	NEMA L21-20P	₩ 😨	(36)C13, (6)C19	1.0 m	AP7564
5	Vertical, 0U	200-240	NAM				 		1	1.0 m	AP7568
울		200-240	NAM	50A, 3Φ	12.5kW	⊛	CS8365C	₩ 🖫	(30)C13, (6)C19	3.0 m	AP7598
e o		200-240	NAM	504.04	44 41.14	_	0000050	₩ 🐨	(24)C13, (4)C19,	1.0 m	AP7569
š		200-240	NAM	50A,3Φ	14.4kW	⊛	CS8365C	®	(2)L6-30	3.0 m	AP7599
208V 3-phase Input		208	NAM	50A, 3Φ	12.5kW	(B)	CS8365C	₩ 🖫	(6)C19, (3)C13	1.8 m	AP7567A
≳	Horizontal, 1U	200-240	NAM	50A, 3Φ	14.4kW	⊗	CS8365C	8	(6)C19	2.4 m	AP7516
2		120/208	NAM	30A, Split Φ	5.8kW	- ŏ	NEMA L14-30P	(9)	(4)L5-20	8.5 m	AP7580
		120/208	NAM	30A, Split Φ	5.8kW	<u>ŏ</u>	NEMA L14-30P	(3)	(4)L6-20	8.5 m	AP7581
	Horizontal, 2U	120/208	NAM	30A, Split Φ	5.8kW	®	NEMA L14-30P	•	(12)5-20	8.5 m	AP7582
		120/208	NAM	30A, Split Φ	5.8kW	- ŏ	NEMA L14-30P	(3)	(4)L5-30	8.5 m	AP7583
		120/208	NAM	30A, Split Φ	5.8kW	<u></u>	NEMA L14-30P	<u> </u>	(4)L6-30	8.5 m	AP7584
- Į		400	EMEA, APJ, LAM, GCN	16A, 3Φ	11kW	@	IEC309-16A 3P+N+PE	₩ 🖫	(36)C13, (6)C19	1.0 m	AP7557
400-415V 3-phase Input	Vertical, 0U	400	EMEA, APJ, LAM, GCN	16A, 3Φ	22kW	0	IEC309-32A 3P+N+PE	₩ 🖫	(6)C19, (3)C13	1.8 m	AP7555A
400 3-pha:		415	NAM	20A, 3Φ	11.5kW	0	IEC309-20A 3P+N+PE	₩ 🖫	(36)C13, (6)C19	1.0 m	AP7557NA
	Horizontal, 1U	400	EMEA, APJ, LAM, GCN	32A, 3Φ	22kW	0	IEC309-32A 3P+N+PE	•	(6)C19	2.4 m	AP7526





AP8000 Series Accessories

Locking IEC output cords



	LOCKING IEC POWER CORDS									
Cord Type 6 per pack	Stra	aight	90 de	Cord Length						
	-									
C13 to C14	AP8702S-NA	AP8702S-WW	AP8702R-NA	AP8702R-WW	0.6m (2ft)					
	AP8704S-NA	AP8704S-WW	AP8704R-NA	AP8704R-WW	1.2.m (4ft)					
	AP8706S-NA	AP8706S-WW	AP8706R-NA	AP8706R-WW	1.8m (6ft)					
C19 to C20	AP8712S		AP8	0.6m (2ft)						
	AP8	714S	AP8	1.2.m (4ft)						
	AP8	716S	AP8	716R	1.8m (6ft)					

90 deg packs include (3each) right & left angled cords NA = CSA, UL Listed WW = CCC, PSE, VDE

Locking IEC input cords

NORTH AMERICAN INPUT CORDS FOR AP8858, AP8958, AP8959 (10 ft.)				
NEMA 5-15P to C19	AP8750			
NEMA 5-20P to C19	AP8751			
NEMA L5-20P to C19	AP8752			
NEMA L6-20P to C19	AP8753			
C20 to C19	AP8760			



INTERNATIONAL INPUT COR AP8858, AP8958, AP8959 (
PSE (Japan) L5-20P to C19	AP8752J
PSE (Japan) L6-20P to C19	AP8753J
Australia AS3112 to C19 (15A)	AP8754
Schuko (CEE 7) to C19	AP8755
UK (BS1363) to C19	AP8756
China (16A) to C19	AP8757
IEC309-16A to C19	AP8758
Bare wire (for field wire) to C19	AP8759
C20 to C19	AP8760

Environmental Sensors





