

P R O F E S S I O N A L R A N G E

Generating sets

Welding sets

Water pumps



Portable Power 50Hz

PPW-PR-DO-US-93



Global Power
Solution™




Power that generates satisfaction.

All over the world, from offshore drilling platforms to extreme desert conditions, from worksites to the most demanding industries, the reliability and performance of its gensets has made SDMO® one of the world's top manufacturers.

Committed to a dynamic of continuous improvement, the SDMO® team spends every day devising and producing gensets that are even more efficient, operate for longer, and are cleaner and easier to maintain and operate.

Its knowledge of the specificities of every use married with innovation and high technology enables SDMO® to offer an unrivalled selection of generating sets ranging from 1 to 5.000 kW. With SDMO® you get 40 years of experience and the service guarantee of a specialist who will always have parts available.

Therefore, whatever your business or whatever your requirements you can be sure that when you choose an SDMO® power source, you are benefiting from the commitment to quality and safety of a large French manufacturer in conformity with the strictest standards: a guarantee for man and machine.



SDMO Industries exports its products to more than 180 countries via its large network of distributors, its 4 offices and its 7 subsidiaries.

- SDMO Energy Ltd in Great Britain,
 - SDMO Industries Ibérica in Spain,
 - SDMO ns/sa in Belgium,
 - SDMO Argentina SA in Argentina,
 - SDMO Do Brasil in Brazil,
 - SDMO Lagos in Nigeria,
 - SMDMO Generating Sets in the USA.
- Distributors / Service Centres
● Head Office



SDMO®, The specialist across all ranges.

Portable Power

Handy and efficient sums up the spirit of a range that fulfils the extremely varied needs of the professional market without sacrificing safety.

Residential Power

Comfort, silence and safety are the catchphrases of this home-focused range. Designed to automatically take over in the event of a power cut and ensure the uninterrupted operation of all household appliances, this range is all about comfort.

Power Products

Performance and power come together for this standard range geared towards the most specialised professional applications. Combined with highly responsive services, such as the X-PRESS delivery solution, this range enables a genset to be dispatched to anywhere in the world within a very short timeframe.

Rental Power

Versatility, sturdiness and silence, all essential criteria for a range suited to the rental market and whose level of performance responds to usage conditions that are both specific and intensive.



Generating sets

4

PRESTIGE range	6
INTENS range	8
TECHNIC range	10
DIESEL range	12
INDUSTRIAL range	14



Welding sets

16

WELDARC™ INTENS range	18
WELDARC™ DIESEL range	20



Water pumps

22

AQUALINE™ INTENS range	24
AQUALINE™ SPECIALIST range	26



Options

28

Portable Power®: SDMO®'s promise.

Safety and quality



In order to enable consumers to make an informed choice, generating set (< 10 kW) and welding set manufacturers have signed up to the Qualigen charter on compliance with applicable regulations and European standards, particularly in the following areas:

- User safety
- Product information
- Noise level
- After Sales Service
- Rating

Health and environment



All the products, accessories and options in the SDMO® Portable Power range scrupulously comply with the European Reach regulations requiring manufacturers and importers to ensure that they only manufacture, sell, import and use substances that are non harmful to human health or the environment. These provisions are based on the principle of precaution.

Noise level

2000/14/EC



The symbol opposite placed near the pictures of our generating sets denotes their compliance with Directive 2000/14/EC on noise levels.

The generating sets shown on white lines in the tables do not comply with this directive.

Responsive and efficient



With its fast acting services division incorporating both the after-sales and spare parts departments, you have the assurance of being able to receive parts whenever and wherever in the world you need them. Using its high performance logistics system and its parts identification tool, SDMO® can locate and dispatch the part you need in the shortest time possible. A permanent stock of 45.000 references guarantees parts availability for all appliances for a period of 10 years.



Generating sets





3 simple, essential steps to choose the right generating set.

1 What will it be used for?


SDMO® designs generating sets that match your needs. There is a range for every purpose: find yours and select the generating set that will give you total satisfaction.

- You need efficient but silent equipment for regular use? You need the **PRESTIGE** range.
- You want tough equipment that can withstand difficult conditions while still being easy to use? The **INTENS** range will meet your needs.
- Are you a professional practising in the field who uses equipment regularly and in an intensive manner? The sturdiness and long operating life of the generating sets in the **TECHNIC** range are made for you..
- You need extremely hardwearing equipment with a long continuous run time? The **DIESEL** range, also recognised for the long run time of its generating sets, will fulfil your expectations and guarantee quality current.
- Your sites need high performance equipment for regular, intensive and high-powered use: The technology of the **INDUSTRIAL** range offers you a personalised solution, providing you with power that is exceptionally quiet.

2 Determine the rating needed

A According to the appliances you use

To help you choose your genset the illustrated guide below, provided for information purposes only, lists the appliances most often used with generating sets.



B Minimum power rating

Certain appliances have a higher start-up rating than the normal operating rating. You should therefore take this into account when making your choice.

To calculate the power you need at start-up, apply the multiplier coefficient provided, for information purposes only, in the below table.

To find out the minimum capacity of your appliances, refer to the manufacturer's technical documentation or ask your SDMO® reseller for advice.

- Equipment with small motors:** coefficient 1.2
- Equipment with large motors:** coefficient 3.5
- Resistive devices:** coefficient 1

COEFFICIENT	PMR
Vibrating needle	2
Vacuum cleaner	1.2
Cement mixer	3.5
Forced air heating	2
Air conditioning unit	3.5
Furnace (mobile)	1.2
Plastering machine	3.5
Mixer	2
Grinder	1.2
Mini display cooler	3.5
Hoist	2
Fluorescent lamp	3.5
High-pressure washer	3.5
Inverter	3.5
Drill	1.2
Drill / breaker	3.5
Belt sander	1.2
Plane	1.2
Refrigerator and freezer	3.5
Circular saw	1.2


Example: to power a 1.000W drill, you will need a generating set of 1.500W (1.000W x 1.2).

3 Make your selection

You have defined your type of use and the output needed: you can now select your generating set in full knowledge of the facts.

PRESTIGE

Silent efficiency



BOOSTER 1000



BOOSTER 2000



ALIZE® 3000



ALIZE® 6000 E



ALIZE® 7500 TE



SDMO
FEATURE

The Inverter technology


This technology guarantees voltage and frequency stability of the genset of + or - 1% of the rating. Such high precision enables high quality current to be supplied, which allows for the most demanding appliances to be used without risk.

Available for the **BOOSTER 1000** and **BOOSTER 2000**.




BOOSTER 1000

0.9 kW - 0.9 kVA⁽¹⁾ - 230 V
HONDA® OHV - GXH 50 engine
Oil level shutdown
Circuit breaker
Run time: 6.3 hours
Weight: 14 kg
Equipped with an adjustable 2 speed ("fast/slow") engine.
Equipped with a 12V output.




ALIZE® 3000

2.8 kW - 3.5 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 200 engine
Oil level shutdown
Circuit breaker
Run time: 9.2 hours
Weight: 46 kg



ALIZE® 6000 E

5.6 kW - 6.05 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 390 engine
Oil level shutdown
Circuit breaker
Electric starter
Run time: 9.6 hours
Weight: 130 kg



SINGLE-PHASE GENERATING SETS

Type	50 Hz		Engine							Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x l x h in cm	Weight in Kg	Options ⁽²⁾					Socket codes ⁽³⁾	
	Max power 230V		Brand	Type	Oil level shutdown	Electric start	HP 3-6000 rpm	Run time in hr	Tank in L	230V Circuit breaker	12V output				Trolley kit trailer	Earth fault protection	Automatic starter box	Manual changeover switch	Cover		
	kW ISO 8528	kVA ⁽¹⁾																			
BOOSTER 1000	0.9	0.9	Honda® OHV	GXH 50	•	X	NC	6.3	3.8	•	•	89	66	46.5 x 26.5 x 38	14	X	X	X	R05M	X	P1U
BOOSTER 2000	1.7	1.7	Honda® OHV	GX 100	•	X	NC	7.0	7.7	•	•	93	70	56 x 34 x 41.5	22	X	X	X	R05M	X	P1N
ALIZE 3000	2.8	3.5	Honda® OHV	GX 200	•	X	5.5	9.2	12	•	X	94	71	57 x 45 x 46	46	R06	X	X	R05M	X	P1L
ALIZE 6000 E	5.6	6.05	Honda® OHV	GX 390	•	•	11	9.6	24	•	X	91	68	78 x 59 x 75.5	130	•*	R02B	R05C	R05M	X	P1P


THREE-PHASE GENERATING SETS

Type	50 Hz			Engine							Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x l x h in cm	Weight in Kg	Options ⁽²⁾				Socket codes ⁽³⁾	
	Max power			Brand	Type	Oil level shutdown	Electric start	HP 3-6000 rpm	Run time in hr	Tank in L	230 V Circuit breaker	400 V Circuit breaker				Trolley kit trailer	Earth fault protection	Automatic starter box	Maintenance kit		
	3-ph 400 V kW ISO 8528	1-ph 230V kVA ⁽¹⁾	kW ISO 8528																		
ALIZE 7500 TE	5.6	6.6	2.3	Honda® OHV	GX 390	•	•	11	9.6	24	•	•	91	68	78 x 59 x 75.5	132	•*	R03B	R05C	X	P1Q

X Not available. • Standard. NC not communicated. ** 4 wheels fitted on frame. (1) Theoretical value calculated for comparison purposes. (2) Refer to the socket information on page 31. (3) Refer to the options information on pages 29 and 30.

INTENS

Exceptionally robust



HX 2500



HX 3000



HX 4000



HX 5000 T



HX 6000



HX 6080



HX 7500 T



**SDMO
FEATURE**

Compliance of standard ranges, C and S

There are specific requirements for generating sets for both EEC and non-EEC markets, particularly in relation to compliance with standards.

In order to be able to offer products suited to these markets, SDMO® generating sets use HONDA® engines, which are adapted to comply with the requirements of the relevant market.

The standard range complies with all European standards and Directives.


The C range complies with EC Directives as well as with Directive 97/68/EC relating to levels of gaseous pollutants. However, it does not comply with Directive 2000/14/EC relating to noise levels.

The S range does not comply with any of these European directives.




HX 3000

3 kW - 3.75 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 200 engine
Oil level shutdown
Circuit breaker
Run time: 2.4 hours
Weight: 41 kg




HX 4000

4 kW - 4.5 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 270 engine
Oil level shutdown
Circuit breaker
Run time: 2.5 hours
Weight: 56 kg



HX 6080

6 kW - 7.5 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 390 engine
Oil level shutdown
Circuit breaker
Run time: 2.4 hours
Weight: 76 kg



SINGLE-PHASE GENERATING SETS

Type	50 Hz		Engine							Alternator			Options ⁽³⁾										C range	S range
	Max power 230V		Brand	Type	Oil level shutdown	Electric start	HP 3,600 rpm	Run time in hr	Tank in L	230V Circuit breaker	12V output	EEC noise level Lwa dB(A) @ 7 m	Dimensions L x W x H in cm	Weight in Kg	Trolley kit trailer	Earth fault protection	Quicklock	Manual changeover switch	Cover	Kit emersion	Socket codes ⁽²⁾			
	kW ISO 8528	kVA ⁽¹⁾																						
HX 2500	2.2	2.4	Honda® OHV	GX 160	•	X	4.8	3.4	3.1	•	X	94	71	59 x 46 x 43	38	R06	R01B	R15	R05M	RHO	R18	P1L	X	X
HX 3000	3.0	3.75	Honda® OHV	GX 200	•	X	5.5	2.4	3.1	•	X	95	72	59 x 46 x 43	41	R06	R01B	R15	R05M	RHO	R18	P1L	Δ	Δ
HX 4000	4.0	4.5	Honda® OHV	GX 270	•	X	8	2.5	5.3	•	X	97	74	71.5 x 57 x 49	56	R07	R01B	R25	R05M	X	R19	P1L	Δ	X
HX 6000	6.0	6.6	Honda® OHV	GX 390	•	X	11	2.4	6.1	•	X	97	74	77 x 57 x 59	79	R07	R02	X	R05M	X	R19	P1H	Δ	Δ
HX 6080 ⁽⁴⁾	6	7.5	Honda® OHV	GX 390	•	X	11	2.4	6.1	•	X	97	74	77 x 57 x 59	76	R07	R02	X	R05M	X	R19	P1H	Δ	Δ


THREE-PHASE GENERATING SETS

Type	50 Hz			Engine							Alternator		Options ⁽³⁾										C range	S range
	Max power			Brand	Type	Oil level shutdown	Electric start	HP 3,600 rpm	Run time in hr	Tank in L	230 V	400 V	EEC noise level Lwa dB(A) @ 7 m	Dimensions L x W x H in cm	Weight in Kg	Trolley kit trailer	Earth fault protection	Maintenance kit	Socket codes ⁽²⁾					
	3-ph 400 V kW ISO 8528	1-ph 230V kVA ⁽¹⁾	1-ph 230V kW ISO 8528																					
HX 5000 T	4	5.0	2.3	Honda® OHV	GX 270	•	X	8	2.5	5.3	•	•	97	74	71.5 x 57 x 49	68	R07	R03	R19	P1J	Δ	X		
HX 7500 T	6	7.5	2.3	Honda® OHV	GX 390	•	X	11	2.4	6.1	•	•	97	74	77 x 57 x 59	80	R07	R03	R19	P1J	Δ	Δ		

X Not available. • Standard. Δ Available. (1) Theoretical value calculated for comparison purposes. (2) Refer to the socket information on page 31. (3) Refer to the options information on pages 29 and 30. (4) Oversized alternator with extremely low harmonics significantly limiting the voltage and frequency variation of the output current while still handling high loads on startup.

TECHNIC

Robust continuous operation no matter where you are



SH 2500



SH 3000



SH 4000



SH 6000
SH 6000 E



SH 7500 T
SH 7500 TE



TECHNIC 10000 E



TECHNIC 15000 TE



**SDMO
FEATURE**

Kohler® engine

Highly efficient, robust and already widely proven worldwide within the agricultural and industrial sectors, this electric starting engine offers peace of mind with automatic shut down in the event of low oil pressure. Maintenance is reduced thanks to automatic valve clearance adjustment.


When there is no call for power for 2 min, the automatic idle adjustment reduces engine speed from 3.000 to 2.400 rpm, which reduces fuel consumption by approximately 50 % and cuts the noise level by 4!

Available for the **TECHNIC 10000 E** and **15000 TE**.




SH 3000

3 kW - 3.75 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 200 engine
Oil level shutdown
Circuit breaker
Run time: 9.2 hours
Weight: 41 kg



SH 6000

6 kW - 6.6 kVA⁽¹⁾ - 230 V
HONDA® OHV - GX 390 engine
Oil level shutdown
Circuit breaker
Run time: 8 hours
Weight: 81 kg



TECHNIC 10000 E

10 kW - 12.5 kVA⁽¹⁾ - 230 V
KOHLER® - CH640S engine
Oil level shutdown
Circuit breaker
Electric starter
Run time: 8.3 hours
Weight: 139 kg



SINGLE-PHASE GENERATING SETS

Type	50 Hz		Engine								Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x w x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽⁴⁾	C range	S range	
	kW ISO 8528	kVA ⁽¹⁾	Brand	Type	Oil level shutdown	Electric start	HP 3.600 rpm	Run time in hr	Tank in L	230V Circuit breaker	12V output	Options ⁽³⁾												
												Trolley kit trailer				Earth fault protection	Automatic starter box	Manual changeover switch	Cover	Maintenance kit				
SH 2500	2.2	2.4	Honda® OHV	GX 160	•	X	4.8	13.3	12	•	X	94	71	59 x 46 x 43	38.5	R06	R01	X	R05M	RHO	X	P1L	X	X
SH 3000	3.0	3.75	Honda® OHV	GX 200	•	X	5.5	9.2	12	•	X	94	71	59 x 46 x 43	41	R06	R01	X	R05M	RHO	X	P1L	X	X
SH 4000	4.0	4.5	Honda® OHV	GX 270	•	X	8	5.7	12	•	X	94	71	71.5 x 57 x 49	64	R07	R01	X	R05M	X	X	P1L	X	X
SH 6000	6.0	6.6	Honda® OHV	GX 390	•	X	11	8	20	•	X	97	74	77 x 57 x 59	81	R07	R02	X	R05M	X	R19	P1H	Δ	Δ
SH 6000 E	6.0	6.6	Honda® OHV	GX 390	•	•	11	8	20	•	X	97	74	77 x 57 x 59	87	R07	R02	R05A	R05M	X	R19	P1H	X	Δ
NEW TECHNIC 10000 E	10	12.5	Kohler®	CH 640S	•	•	20	8.3	35	•	X	101	78	89.5 x 57 x 77	139	R07A	R02B	R05A	R05M	X	X	P1E	X	X


THREE-PHASE GENERATING SETS

Type	50 Hz			Engine								Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x w x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽⁴⁾	C range	S range
	Max power		Brand	Type	Oil level shutdown	Electric start	HP 3.600 rpm	Run time in hr	Tank in L	230 V Circuit breaker	400 V Circuit breaker	Options ⁽³⁾												
	3-ph 400 V kW ISO 8528	1-ph 230V kVA ⁽¹⁾										Trolley kit trailer	Earth fault protection				Automatic starter box	Maintenance kit						
SH 7500 T	6.0	7.5	2.3	Honda® OHV	GX 390	•	X	11	8	20	•	•	97	74	77 x 57 x 59	83	R07	R03B	X	R19	P1I	Δ	Δ	
SH 7500 TE	6.0	7.5	2.3	Honda® OHV	GX 390	•	•	11	8	20	•	•	97	74	77 x 57 x 59	89	R07	R03B	R05A	R19	P1I	X	Δ	
NEW TECHNIC 15000 TE	11	13.75	3.7	Kohler®	CH 640S	•	•	20	8.3	35	•	•	101	78	89.5 x 57 x 77	146	R07A	R03B	R05A	X	P1E	X	X	

X Not available. • Standard. NC not communicated. ** 4 wheels fitted on frame. (1) Theoretical value calculated for comparison purposes. (2) Refer to the socket information on page 31. (3) Refer to the options information on pages 29 and 30. Those generating sets shown on a white line do not conform to the 2000/14/EC Directive and should therefore only be used inside a building or in countries where the Directive does not apply (countries that are not members of or affiliated to the E.U.).

DIESEL

Durable with an extended continuous run time



DIESEL 3000



DIESEL 4000
DIESEL 4000 E



DIESEL 6000 E



DIESEL 6500 TE



DIESEL 10000 E



DIESEL 15000 TE



DX 6000 E
DX 6000 TE



SD 6000 E
SD 6000 TE



**SDMO
FEATURE**

Electric starter and low oil safety cut-off on the DIESEL generating sets

With this feature, not only does the engine start and stop with a simple turn of a key but, more importantly, it will not start and will not stop of its own accord running if the oil pressure (for **DIESEL 10000 E** and **15000 TE** models) or the oil level (for the **SD 6000 E**, **SD 6000 TE**, **DIESEL 4000 E**, **DIESEL 6000 E**, **DIESEL 6500 TE** models) is too low. All 4 and 6 kW models, excluding SD models, feature pull-cord starting in the event of a flat battery.



MICS MODYS - SD 6000 E



NEW

DIESEL 4000 E

3.4 kW - 4.25 kVA⁽¹⁾ - 230 V
 KOHLER® DIESEL KD 350 engine
 Oil level shutdown
 Circuit breaker
 Run time: 4.8 hours
 Weight: 81 kg



LWA 108 / 85 dB(A) @ 7m



2 year engine warranty



SD 6000 E

5.2 kW - 6.5 kVA⁽¹⁾ - 230 V
 YANMAR® DIESEL OHV - L100 engine
 Oil level shutdown
 Circuit breaker
 Electric starter
 Run time: 20 hours
 Weight: 187.5 kg



2000/14/EEC
 Lwa
 95



LWA 95 / 72 dB(A) @ 7m



NEW

DIESEL 10000 E


9 kW - 11.25 kVA⁽¹⁾ - 230 V
 KOHLER® DIESEL - KD425-2 engine
 Oil level shutdown
 Circuit breaker
 Electric starter
 Run time: 16.5 hours
 Weight: 162 kg



LWA 109 / 86 dB(A) @ 7m



2 year engine warranty



SINGLE-PHASE GENERATING SETS

Type	50 Hz		Brand	Type	Engine					Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x l x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽²⁾
	Max power 230V				Oil level shutdown	Electric start	HP 3,600 rpm	Run time in hr	Tank in L	230V Circuit breaker	12V output				Trolley kit trailer	Earth fault protection	Automatic starter box	Manual changeover switch		
	kW ISO 8528	kVA ⁽¹⁾																		
NEW DIESEL 3000	2.4	3.0	Kohler® Diesel	KD 225	X	X	4.5	5	3	•	X	107	84	65 x 51 x 52	55	R06B	R01C	X	R05M	P1L
NEW DIESEL 4000	3.4	4.25	Kohler® Diesel	KD 350	X	X	7	4.8	4.3	•	X	108	85	81 x 55.5 x 59	70	R07B	R01	X	R05M	P1L
NEW DIESEL 4000 E	3.4	4.25	Kohler® Diesel	KD 350	•	•	7	4.8	4.3	•	X	108	85	81 x 55.5 x 59	81	R07B	R01	R05A	R05M	P1L
NEW DIESEL 6000 E	5.2	6.5	Kohler® Diesel	KD 440	•	•	9.8	4.2	5	•	X	108	85	81 x 55.5 x 59	100	R07B	R02	R05A	R05M	P1H
NEW DIESEL 10000 E	9.0	11.25	Kohler® Diesel	KD425-2	•	•	19	16.5	35	•	X	109	86	89.5 x 57 x 77	162	R07A	R02B	R05A	R05M	P1B
DX 6000 E	5.2	6.5	Yanmar® OHV	L100	•	•	10	9.2	12	•	X	106	83	87 x 57 x 55.5	105	R07	R02	R05A	R05M	P1H
SD 6000 E ⁽⁵⁾	5.2	6.5	Yanmar® OHV	L100	•	•	10	20	26	•	X	95	72	95.1 x 79 x 112.5	187.5	•	R02B	R05A	R05M	P1D


THREE-PHASE GENERATING SETS

Type	50 Hz			Brand	Type	Engine					Alternator		EEC noise level Lwa dB(A) @ 7 m	Dimensions L x l x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽²⁾
	Max power					Oil level shutdown	Electric start	HP 3,600 rpm	Run time in hr	Tank in L	230 V Circuit breaker	400 V Circuit breaker				Trolley kit trailer	Earth fault protection	Automatic starter box			
	3-ph 400 V kW ISO 8528	1-ph 230V kVA ⁽¹⁾	kW ISO 8528																		
NEW DIESEL 6500 TE	5.2	6.5	2.3	Kohler® Diesel	KD 440	•	•	9.8	4.2	5	•	•	108	85	81 x 55.5 x 59	105	R07B	R03	R05A	P1J	
NEW DIESEL 15000 TE	10	12.5	3.7	Kohler® Diesel	KD 425-2	•	•	19	16.7	35	•	•	109	86	89.5 x 57 x 77	169	R07A	R03B	R05A	P1E	
DX 6000 TE	5.2	6.5	2.3	Yanmar® OHV	L100	•	•	10	9.2	12	•	•	106	83	87 x 57 x 55.5	106	R07	R03	R05A	P1J	
SD 6000 TE ⁽⁵⁾	5.2	6.5	2.3	Yanmar® OHV	L100	•	•	10	20	26	•	•	95	72	95.1 x 79 x 112.5	188.5	•	R03B	R05A	P1G	

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (2) Refer to the socket information on page 31. (3) Refer to the options information on pages 29 and 30. (5) MICS MODYS. Those generating sets shown on a white line do not conform to the 2000/14/EEC Directive and should therefore only be used inside a building or in countries where the Directive does not apply (countries that are not members of or affiliated to the E.U.).

INDUSTRIAL

When you need the best performance



XP-T6KM-ALIZÉ®



XP-T8HKM-ALIZÉ®



XP-T9KM-ALIZÉ®



XP-T9HK-ALIZÉ®



XP-T12K-ALIZÉ®



XP-T12HK-ALIZÉ®



XP-T15HK-ALIZÉ®



XP-T16K-ALIZÉ®



SDMO
FEATURE

NEXYS control panel

Featuring a polycarbonate front panel and an LCD screen, this quality, ergonomically designed control panel facilitates simple and reliable control of your generating set. The screen displays the genset's main electrical and mechanical parameters.

All generating sets in this range come with this control panel.




XP-T6KM-ALIZÉ®

5.5 kW - 6 kVA⁽¹⁾ - 230 V
MITSUBISHI® DIESEL L3E-SD
1.500 rpm engine
Oil level shutdown
Circuit breaker
Electric starter
Run time: 29.4 hours
Weight: 390 kg



XP-T8HKM-ALIZÉ®

7.5 kW - 9.35 kVA⁽¹⁾ - 230 V
MITSUBISHI® DIESEL L2E-SDH
3.000 rpm engine.
Oil level shutdown
Circuit breaker
Electric starter
Run time: 19.2 hours
Weight: 340 kg



XP-T12K-ALIZÉ®

9.2 kW - 11.5 kVA⁽¹⁾ - 230 V
MITSUBISHI® DIESEL S3L2-SD
1.500 rpm engine
Oil level shutdown
Circuit breaker
Electric starter
Run time: 20 hours
Weight: 535 kg



M = single-phase (ex = XP-T9KM-ALIZÉ®)
H = 3.000 rpm (ex = XP-T15HK-ALIZÉ®)

SINGLE-PHASE GENERATING SETS

50 Hz			Engine						Alternator		EEC Noise level Lwa dB(A) @ 7 m	Dimensions Lxw x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽²⁾	
Type	Max power 230V		Brand	Type	Oil level shutdown	Electric start	Run time in hr	Tank in L	230V Circuit breaker	12V output				Road trailer	Earth fault protection	Automatic starter box	Manual changeover switch	Commissioning		
	kW ISO 9528	kVA ⁽¹⁾																		
XP-T6KM-ALIZÉ ⁽⁴⁾	5.5	6	Mitsubishi® Diesel	L3E-SD	•	•	29.4	50	•	X	86	59	150 x 76 x 103	390	R08B	•	R05B	R05M	RMS	P1C
XP-T8HKM-ALIZÉ ⁽⁴⁾	7.5	9.35	Mitsubishi® Diesel	L2E-SDH	•	•	19.2	50	•	X	94	68	150 x 76 x 103	340	R08B	•	R05B	R05M	RMS	P1C
XP-T9KM-ALIZÉ ⁽⁴⁾	8.6	10.75	Mitsubishi® Diesel	S3L2-SD	•	•	20	50	•	X	86	60	175 x 77.5 x 123	544	R08C	•	R05B	R05M	RMS	P1C

THREE-PHASE GENERATING SETS

50 Hz			Engine						Alternator		EEC Noise level Lwa dB(A) @ 7 m	Dimensions Lxw x h in cm	Weight in Kg	Options ⁽³⁾					Socket codes ⁽²⁾
Type	Max power		Brand	Type	Oil level shutdown	Electric start	Run time in hr	Tank in L	230 V Circuit breaker	400 V Circuit breaker				Road trailer	Earth fault protection	Automatic starter box	Commissioning		
	3-ph 400 V	kW ISO 9528																kVA ⁽¹⁾	
XP-T9HK-ALIZÉ ⁽⁴⁾	7.2	9	Mitsubishi® Diesel	L2E-SDH	•	•	19.2	50	•	•	94	68	150 x 76 x 103	360	R08B	•	R05B	RMS	P1F
XP-T12K-ALIZÉ ⁽⁴⁾	9.2	11.5	Mitsubishi® Diesel	S3L2-SD	•	•	20	50	•	•	86	60	175 x 77.5 x 123	535	R08C	•	R05B	RMS	P1V
XP-T12HK-ALIZÉ ⁽⁴⁾	9.6	12	Mitsubishi® Diesel	L3E-SDH	•	•	11.9	50	•	•	95	69	150 x 76 x 103	380	R08B	•	R05B	RMS	P1V
XP-T16K-ALIZÉ ⁽⁴⁾	12.8	16	Mitsubishi® Diesel	S4L2-SD	•	•	14.7	50	•	•	87	61	175 x 77.5 x 123	554	R08C	•	R05B	RMS	P1V
XP-T15HK-ALIZÉ ⁽⁴⁾	12	15	Mitsubishi® Diesel	L3E-SDH	•	•	11.9	50	•	•	96	71	175 x 77.5 x 123	442	R08C	•	R05B	RMS	P1V

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (2) Refer to the sockets information on page 31. (3) Refer to the options information on pages 29 and 30. (4) MICS NEXYS.



Welding set





3 criteria for selecting the right welding set.

Essential for welding on worksites without electricity or when carrying out maintenance on isolated machines, WELDARC™ welding sets are practical, easy to transport and ready to use in record time. They can also be used as auxiliary generating sets for the supply of electricity.

With the standard integration of the Kohler engines in the WELDARC™ 300 TE and WELDARC™ 300 TDE, these welding sets offer technological expertise that brings together power and performance, safety and robustness with reduced maintenance and operating costs.

1 Frequency of use

A DC voltage welding set, like those in the WELDARC™ range, will enable you to use all electrode types and weld even the most technical material. The Diesel versions are particularly suited to intensive use, with their continuous run time extending to almost double that of the petrol versions.

2 The types of electrode you use

Each welding set offers you the choice of a variety of electrodes, which it is essential to specify before selecting your welding set.

→ Rutile

an electrode for general use which is very flexible in use.

→ Cellulosique

an electrode suitable for downward welding.


→ Basic

an electrode for top security technical assembly. This use is recommended for parts under significant mechanical strain. It requires welding using direct current.

The maximum diameter of the welding rod is also an important criterion that you should keep in mind when selecting your welding set. Do not forget to take this into account.

3 The backup power you need

All welding sets in the WELDARC™ range can supply electrical current through their auxiliary outputs. They can be used as standard electricity generating sets and the choice of model for this function is subject to the same criteria as the other electricity generating sets in the Portable Power range.



WELDARC™ INTENS

The welding solution for worksites without electricity



VX 200/4 H



VX 220/7.5 H



WELDARC 300 TE



SDMO
FEATURE

Kohler® engine

Recognised for its efficiency and robustness, widely tested in the agricultural, industrial and maritime sectors, the Kohler engine is installed in the new WELDARC™ 300 TE welding set.

This engine offers the ergonomics of electric starter, the safety of engine shut down in the event of low oil pressure and extended service intervals thanks to its automatic valve clearance adjustment. Automatic idle adjustment also makes it even more economical to run.



VX 200/4H

Direct current
Welding rate: Intensive (60 %): 170 Amp.
Normal (35 %): 200 Amp.

HONDA® OHV - GX 390 engine
Oil level shutdown
Max. Ø rod 4 mm
Auxiliary output: 4 kW - 230 V (with circuit breaker)



VX 220/7.5H

Direct current
Welding rate: Intensive (60 %): 170 Amp.
Normal (35 %): 200 Amp.

HONDA® OHV - GX 390 engine
Oil level shutdown
Electric starting
Max. Ø rod 4 mm
Auxiliary output: 7.5 kVA⁽¹⁾ - 400 V (with circuit breaker)



WELDARC 300 TE

Direct current
Welding rate: Intensive (60 %): 250 Amp.
Normal (35 %): 300 Amp.

KOHLER® CH 640S engine
Oil level shutdown
Max. Ø rod 5 mm
Auxiliary outlet: 8 kVA⁽¹⁾ - 400 V (with circuit breaker)



WELDING SETS

Type	Engine		Source auxiliary		Welding rate		Adjustments		Rods		Max. starting current	Nominal	EEC Noise level in Lwa	dB(A) @ 7m	Dimensions l x w x h in cm	Weight in Kg	Options ⁽³⁾				Socket codes ⁽²⁾	C range	S range		
	Brand	Type	Run time in hr	Fuel tank in L	230 V kW ISO 8528	400 V kVA ⁽¹⁾	60% intensive	35% Normal	Min/max amperage	Current							Min/max Ø in mm	All types	Trolley kit	Earth fault protection				Maintenance kit	Welding kit
VX 200/4H	Honda®	OHV GX 390	2.4	6.1	4.0	-	170 A	200 A	50-200 A	Direct	1.6-4	Yes	75 V	230 V	97	74	88 x 57 x 55.5	87	R07	R01	R19	R10	P1L	Δ	Δ
VX 220/7.5H	Honda®	OHV GX 390	2.4	6.1	3.5	7.5	170 A	200 A	40-200 A	Direct	1.6-4	Yes	73 V	400 V	97	74	88 x 57 x 55.5	88	R07	X	R19	R10	P1J	Δ	Δ
NEW WELDARC 300 TE	Kohler®	CH 640S	9.2	35	3.0	8.0	250 A	300 A	40-300 A	Direct	1.6-5	Yes	75 V	400 V	101	78	89.5 x 57 x 77	152	R07A	•	X	R10	P1K	X	X

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (2) Refer to the sockets information on page 31. (3) Refer to the options information on pages 29 and 30.

Those generating sets shown on a white line do not conform to the 2000/14/EC Directive and should therefore only be used inside a building or in countries where the Directive does not apply (countries that are not members of or affiliated to the E.U.).

WELDARC™ DIESEL

Long continuous run time for lengthy welding projects



VX 180/4 DE



WELDARC 300 TDE



SDMO
FEATURE

Intensive power

The ideal choice for repairing large machinery and agricultural or site vehicles in isolated areas, the Weldarc™ 300 TDE welding set offers exceptional welding quality. It is powerful, meaning it can be used for long periods of time without overheating and to weld components of more than 1cm thickness.



VX 180/4 DE

Direct current
Welding rate: Intensive (60 %): 145 Amp
Normal (35 %): 180 Amp
YANMAR® OHV L100 engine
Oil level shutdown
Max. Ø rod 4 mm
Auxiliary output: 4 kW - 230 V
(with circuit breaker)



WELDARC 300 TDE

Direct current
Welding rate: Intensive (60 %): 250 Amp
Normal (35 %): 300 Amp
KOHLER® DIESEL KD425-2 engine
Oil level shutdown
Max. Ø rod 5 mm
Auxiliary output: 8 kVA⁽¹⁾ - 400 V
(with circuit breaker)



WELDING SETS

Type	Engine				Source auxiliary		Welding rate		Adjustments		Rods		Max. Starting current	Nominal	EEC Noise level in Lwa		Dimensions l x w x h in cm	Weight in Kg	Options ⁽³⁾			Socket codes ⁽²⁾	
	Brand	Type	Run time in hr	Tank in L	230 V	400 V	60% Intensive	35 % (normal)	Min/max ampereage	Current	Min/max Ø in mm	All types			dB (A) @ 7m	dB (A) @ 7m			Trolley kit	Earth fault protection	Welding kit		Socket codes ⁽²⁾
VX 180/4 DE	Yanmar®	OHV	L100	9.2	12	4	-	145 A	180 A	50-180 A	Direct	1.6-4	Yes	75 V	230 V	106	83	87 x 57 x 55.5	118	R07	R01	R10	P1L
WELDARC 300 TDE	Kohler®	Diesel	KD425-2	20.6	35	3	8	250 A	300 A	40-300 A	Direct	1.6-5	Yes	75 V	400 V	109	86	89.5 x 57 x 77	175	R07A	•	R10	P1K

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (2) Refer to the sockets information on page 31. (3) Refer to the options information on pages 29 and 30.

Those generating sets shown on a white line do not conform to the 2000/14/EC Directive and should therefore only be used inside a building or in countries where the Directive does not apply (countries that are not members of or affiliated to the E.U.).



Water pumps





3 essential steps to choosing the right water pump.

1 Assess the nature of the water to be processed


Since all liquids needing pumping do not share the same characteristics, SDMO® water pumps are designed for multiple purposes depending on:

- **The quality of the water:** clear water and water with little sediment or heavily sediment. For special liquids (sea water, liquid fertiliser, hydrocarbons ...), ask your SDMO® retailer for advice.
- **The flow and pressure** required depending on the head losses.

2 Calculate the height of the elevation required

The elevation is more or less important depending on the configuration of the installation or the application (pumping out, spinkling, irrigation, draining, washing). It is calculated from:

- **The suction height:**
This is the difference in height between the level of the water to be pumped and the axle of the pump. The laws of physics dictate that this cannot exceed 8m above sea level.
- **The discharge height**
This is the difference in height between the axle of the pump and the highest point of the network.
- **The head loss**
This is the resistance encountered by the water in the pipes. It is calculated according to the length, diameter and quality of the pipes, their shapes and the number of accessories (for general cases, we take 20%).



Height of elevation = suction height + height of lift + head loss

3 Determine the flow to choose the right output

The flow corresponds to the maximum quantity of water that can be extracted at a given height. It is determined by checking the height of elevation in metres on the curve. The flow in L/min may then be deduced. The height of elevation determines the available pressure. This is divided by 10 to obtain the pressure in bar. If this pressure is not enough, a more powerful model should be selected.

The flow and the discharge height are the main criteria used in selecting your water pump.

TECHNICAL CHARACTERISTICS

Range	Model	Helix	Impeller	Mechanical seal	Ease of removal
AQUALINE™ INTENS	ST 2.36 H	Graphite cast iron	Cast iron	Ceramic carbon	•
	ST 3.60 H	Graphite cast iron	Cast iron	Ceramic carbon	•
	TR 2.36 H	Graphite cast iron	Graphite cast iron	Ceramic carbon	••
	TR 3.60 H	Graphite cast iron	Graphite cast iron	Ceramic carbon	••
AQUALINE™ SPECIALIST	HP 2.26 H	Graphite cast iron	Graphite cast iron	Ceramic carbon	•
	XC 2.34 H	PET*	PET*	Ceramic carbon	•
	XT 3.78 H	Graphite cast iron	Graphite cast iron	Ceramic carbon	•••
	TRASH 4	Graphite cast iron	Graphite cast iron	Ceramic carbon	•••

• Tool required •• Tool supplied ••• Without tool * PolyEthylène Terephthalate
Silicon carbide: Better abrasion resistance, more durable and less maintenance.
Graphite cast iron: Harder, more resistant material, giving greater protection against abrasion from matter sucked in.

AQUALINE™ INTENS

Designed for water with low solid content



CLEAR 1



ST 2.36 H



ST 3.60 H



TR 2.36 H



TR 3.60 H



Filter, clamps and screw connectors.



Included with ST 2.36 H and CLEAR 1



Included with ST 3.60 H



Included with TR 2.36 H




Included with TR 3.60 H



NEW


CLEAR 1

Ø: 1" - 25 mm • Flow: 6.6 m³/h
Maximal pressure: 3 bar
Run time: 1 hour
Height of elevation: 30 m
MITSUBISHI® TLE 20
(2 stroke) engine
Weight: 4.9 kg




ST 3.60 H

Ø: 3" - 80 mm
Flow: 54 m³/h
Maximal pressure: 2.6 bar
Run time: 4.3 hours
Height of elevation: 26 m
HONDA® GX 160
Weight: 29 kg



TR 2.36 H

Ø: 2" - 50 mm
Flow: 36 m³/h
Maximal pressure: 2.9 bar
Run time: 2 hours
Height of elevation: 29 m
HONDA® OHV GX 120 engine
Weight: 23 kg



WATER PUMPS

Type	Pump							Engine					Dimensions L x W x H in cm	Weight in kg	Accessories			Options ⁽³⁾			
	Suction Ø in mm	Lift Ø in mm	Height of elevation in m	Max flow in m ³ /hr	Max flow in L/min	Max suction height in m	Granulometry in mm	Automatic priming	Brand	Type	HP 3.600 in rpm	Tank in L			Oil level shutdown	Input/output connectors	Filter	Clamp	Cover	Hose kit	Rapid connectors
NEW CLEAR 1	25	25	30	6.6	110	8	8	Yes	Mitsubishi®	TLE 20 (2 stroke)	0.8	0.4	X	29 x 24.5 x 31.9	4.9	2	1	3	X	•	X
ST 2.36 H	50	50	29	36	600	8	8	Yes	Honda®	GX 120	3.5	2	Yes	46.8 x 36.2 x 38	23	2	1	3	RHO	R11	R13
ST 3.60 H	80	80	26	54	970	8	8	Yes	Honda®	GX 160	4.8	3.1	Yes	50.5 x 41.4 x 44.8	29	2	1	3	RHO	R12	R14
TR 2.36 H	50	50	29	36	600	8	8	Yes	Honda® OHV	GX 120	3.5	2	Yes	46.8 x 36.2 x 39.8	23	2	1	3	RHO	R11	R13
TR 3.60 H	80	80	26	54	900	8	8	Yes	Honda® OHV	GX 160	4.8	3.1	Yes	50.5 x 39.8 x 46.6	29	2	1	2	RHO	R12	R14

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (3) Refer to the options information on pages 29 and 30.

AQUALINE™ SPECIALIST

High performance under extreme conditions



HP 2.26 H



XC 2.34 H



XT 3.78 H



TRASH 4



Filter, clamps and screw connectors.



Included with HP 2.26 H and XC 2.34 H



Included with XT 3.78 H



Included with TRASH 4

Pumping of chemical and corrosive products

SDMO
FEATURE


The XC 2.34 H pump is especially recommended for agricultural use, particularly for pumping chemical and corrosive liquids.

Its corrosive resistant construction makes it ideal for pumping salt water.



HP 2.26 H

High pressure pump
Ø: 2" - 50 mm
Flow: 26.4 m³/h
Maximal pressure: 5.7 bar
Run time: 3.4 hours
Height of elevation: 57 m
HONDA® OHV GX 160 engine
Weight: 30 kg




Lance kit - R09 (see page 30)




XC 2.34 H

Ø: 2" - 50 mm
Flow: 33.6 m³/h
Maximal pressure: 2.6 bar
Run time: 2.5 hours
Height of elevation: 26 m
HONDA® OHV GX 120 engine
Weight: 22 kg



TRASH 4

Ø: 4" - 100 mm
Flow: 120 m³/h
Maximal pressure: 1.7 bar
Run time: 4.1 hours
Height of elevation: 17 m
KOHLER® DIESEL KD350 engine
Weight: 92 kg



WATER PUMPS

Type	Pump								Engine				Accessories				Options ⁽³⁾						
	Suction Ø in mm	Lift Ø in mm	Height of elevation in m	Max flow in m³/h	Max flow in L/min	Max suction height in m	Granulometry in mm	Automatic priming	Brand	Type	HP 3.600 in rpm	Tank in L	Oil level shutdown	Dimensions l x w x h in cm	Weight in kg	Input/output connectors	Filter	Clamp	Cover	Hose kit	Trolley kit	Lance kit	Rapid connectors
HP 2.26 H	50	50	57	26.4	440	8	8	Yes	Honda® OHV	GX 160	4.8	3.1	Yes	41.5 x 54.5 x 45.5	30	2	1	2	RHO	X	X	R09	
XC 2.34 H	50	50	26	33.6	560	8	8	Yes	Honda® OHV	GX 120	3.5	2.0	Yes	52 x 42.8 x 44.8	22	2	1	3	RHO	R11	X	X	R13
XT 3.78 H	80	80	27	80.4	1340	8	27	Yes	Honda® OHV	GX 240	7.1	5.3	Yes	69 x 48.5 x 53.2	58	2	1	3	X	R12	X	X	R14
NEW TRASH 4	100	100	17	120	2000	8	28	Yes	Kohler® Diesel	KD350	7	4.3	X	71.5 x 57 x 59	92	2	1	3	X	R21	R07	X	•

X Not available. • Standard. (1) Theoretical value calculated for comparison purposes. (3) Refer to the options information on pages 29 and 30.



Options



Ex works options only

■ Generating set options ■ Welding set options ■ Water pump options

Automatic mains failure panels

Automatic start if there is a power cut.



■ Ref. R05A



■ Ref. R05B



■ Ref. R05C


Differential boxes

■ ■ Ref. R01/R02

This set includes a differential switch and a hour counter.

■ Ref. R03

This set includes a differential switch, a hour counter and a thermal circuit breaker.



■ Ref. R02B/R03B

This set includes a differential switch and 3-phase quadripole (R03B) and single-phase double pole (R02B).

Road trailers

■ Ref. R08B

Unbraker trailer for **XP-T6KM-ALIZÉ**®, **XP-T8HKM-ALIZÉ**®, **XP-T9HK-ALIZÉ**® and **XP-T12HK-ALIZÉ**® (PGVV up to 750 kg with registration). Net weight: 190 kg. Overall dimensions: 2915 x 1546 x 1531 mm. Optional articulated tiller (ask us for details).

■ Ref. R08C

Unbraker trailer for **XP-T9KM-ALIZÉ**®, **XP-T12K-ALIZÉ**®, **XP-T15HK-ALIZÉ**® et **XP-T16K-ALIZÉ**® (PGVV up to 750 kg with registration). Net weight: 115 kg. Overall dimensions: 2885 x 1245 x 1640 mm. Optional articulated tiller or tiller equipped with brake (ask us for details).



Ref. R08C

Options supplied separately

■ Generating set options ■ Welding set options ■ Water pump options

Cans of oil

■ ■ ■ Ref. RBH0.5/RBH1

Box of 24 0.5 l. cans of oil or 20 1l. cans of oil (SAE 15W40).



Manual changeover switch

■ Ref. R05M

The manual changeover switch is used to connected and disconnect a generating set manually to a domestic circuit when there is a power cut.



"Quick'lock" reel

■ Ref. R15/R25

Specially designed to fit your SDMO® generating set, these reels facilitate total freedom of movement thanks to their 20m cable (R15 = 3 x 1.5² H07-RNF et R25 = 3 x 2.5² H07-RNF). For your safety they are fitted with a 30 mA plug with earth fault protection and a thermal circuit breaker incorporated in the coiler.



Options supplied separately *(continued)*


■ Generating set options
 ■ Welding set options
 ■ Water pump options

Trolley kits



■ Ref. R06/R06B

Trolley kit for 2 and 3 kW generating sets.
R06: 1 handle bar.
R06B: 2 handle bars.



Ref. R07

■ ■ Ref. R07/R07A/R07B

Trolley kit with handle bars to facilitate transport of the generating sets.
R07/R07A: 4 handle bars.
R07B: 2 handle bars.

Cover

■ ■ Ref. RHO

Cover for SDMO® generating sets and water pumps.



Maintenance kits

■ ■ ■ Ref. R18

10 maintenance kits for HONDA® GX 200 engines.

■ ■ ■ Ref. R19

10 maintenance kits for HONDA® GX 270 and GX 390 engines..

Each kit includes a can of oil, a spark plug and an air filter.



■ Ref. RMS

Commissioning consists of: verifying compliance of the installation, checking fluid levels, starting the generating set, carrying out no-load and load tests, teaching the customer about care and maintenance of the generating set. Both the technician and the customer confirm acceptance of the commissioning process.

Set of male plug

■ ■ Ref. RPM

Male plugs for all models made up of: 2x16A/230V, CEE17: 1x16A/230V, 1x32A/230V and 1x16A/400V.



Earth spike

■ Ref. RPQ


For earthing your generating set. A 1m long galvanised spike, supplied with 2m of 10 mm² thick cable.



Differential boxes

■ Ref. R01B/R01C

This modular set includes a differential switch and a residential socket.



Welding kit

■ Ref. R10

Includes 1 x 10m cable, 1 earth clip, 1 electrode holder, 1 hammer, 1 brush, 1 mask.



Lance kit



■ Ref. R09

Lance kit for HP 2.26 H water pumps comprising 2 fire hoseconnectors, 25m fire hose, 5m intake hose and a fire-fighting lance (with jet, spray and off).

Hose kit

■ Ref. R11/R12

Hose kit for 2" and 3" water pumps made up of 5m suction + 25m lift.

■ Ref. R21

Hose kit for 4" water pumps made up of 5m suction + 25m lift.



Rapid connectors

■ Ref. R13/R14

Rapid connections kit for 2" and 3" water pumps*.

**Supplied as standard with the 4" pumps.*



SUBSIDIARIES

ARGENTINA

SDMO ARGENTINA S.A.

Tél. +54 114 836 3511

Fax +54 114 836 3516

BELGIUM

SDMO NV/SA

Tél. +32 3 646 04 15

Fax +32 3 646 06 25

BRAZIL

SDMO DO BRASIL

Tél. +55 (11) 4390 8434

Fax +55 (11) 4390 8434

GREAT BRITAIN

SDMO ENERGY LTD

Tél. +44 (0) 1932 345 777

Fax +44 (0) 1932 350 033

NIGERIA

SDMO LAGOS

Tél. +234 (0)1 776 95 95

Fax +33 (0)1 72 27 55 62

SPAIN

SDMO INDUSTRIES IBERICA

Tél. +34 902 30 56 56

Fax +34 93 580 31 36

UNITED STATES

SDMO GENERATING SETS

Tél. +1 305 863 00 12

Fax +1 305 863 97 81

OFFICES

ALGERIA

SDMO ALGER

Tél. +213 21 68 12 12

Fax +213 21 68 14 14

DUBAÏ

SDMO MIDDLE EAST

Tel. +971 50 51 496 83

Fax +33 1 72 27 55 52

RUSSIA

SDMO MOSCOU

Tél. +7 926 838 05 34

Fax +33 (0)1 72 27 55 48

SOUTH AFRICA

SDMO JOHANNESBOURG

Tél. +33 (0)6 31 59 47 01

Fax +33 (0)1 72 27 61 51



ISO 9001



SDMO Industries - French sites



SDMO Industries - 12 bis, rue de la Villeneuve - CS 92848 - 29228 BREST Cedex 2 - France
Tél. +33 (0) 2 98 41 41 41 - Fax +33 (0) 2 98 41 63 07 - Téléx 615 092 F - <http://www.sdmo.com>

S.A.S. with a capital of €17 066 520

